

BRITISH - THREAD

DIN 71412

STAINLESS

British Standard Pipe Tapered (BSPT) threads are a Whitworth tapered thread. These fittings do not have the same leak-free qualities as PTF-type threads. These British tapered threads are covered by DIN 2999. Please note: German fittings are available, and possess the same dimensions as the British fittings listed below.

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE


H2600S

Straight - Stainless
1/8"-28 BSPT



H2610S

Straight - Stainless
R 1/8"




H2601S

45° Angle - Stainless
1/8"-28 BSPT



H2611S

45° Angle - Stainless
R 1/8"




H2602S

90° Angle - Stainless
1/8"-28 BSPT



H2612S

90° Angle - Stainless
R 1/8"




H2603S

Straight - Stainless
1/4"-19 BSPT



H2613S

Straight - Stainless
R 1/4"




H2604S

45° Angle - Stainless
1/4"-19 BSPT



H2614S

45° Angle - Stainless
R 1/4"




H2605S

90° Angle - Stainless
1/4"-19 BSPT




H2615S

90° Angle - Stainless
R 1/4"



Item #	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H2600S	1/8"-28	Straight	.79"	.32"	.23"	—	.38"	—	11.0 mm
H2601S	1/8"-28	45°	.83"	.22"	.15"	.64"	.38"	.43"	11.0 mm
H2602S	1/8"-28	90°	.71"	.22"	.15"	.83"	.38"	.61"	11.0 mm
H2603S	1/4"-19	Straight	.69"	.26"	.15"	—	.51"	—	14.0 mm
H2604S	1/4"-19	45°	.89"	.26"	.15"	.75"	.51"	.47"	14.0 mm
H2605S	1/4"-19	90°	.87"	.26"	.15"	.91"	.51"	.63"	14.0 mm



All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed. Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2019