785.392.3017 FAX 785.392.2845

www.huyett.com



1/4"-28 **SAE-LT**


EXCEEDS 12 HR SALT SPRAY. 8,000 PSI MAX PRESSURE.

SAE J534

Angled fittings are often necessary to allow for maintenance in confined areas, such as on industrial machinery. G.L. Huyett offers angled grease fittings in different degrees to fit your individual need. 1/4"-28 SAE-LT grease fittings have threads that taper toward the end of the shank. When installed, the threads compress into the mated assembly, thus forming a tight seal.

H1637Z3

45° Angle 1/4"-28 Taper Thread Standard Shank




🚹 1637-BI L 5210 L JD7788

AVAILABLE IN STAINLESS

AVAILABLE IN BRASS AVAILABLE IN MONEL®

H1636Z3


45° Angle 1/4"-28 Taper Thread Long Shank



1636

H3010Z3


65° Angle 1/4"-28 Taper Thread Long Shank



🐧 3010-BI 700396

H369575

65° Angle 1/4"-28 Taper Thread Long Shank



TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

M 369575

ltem#	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min.Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H1637Z3	1/4"-28	45°	.82"	.20"	.10"	.58"	.25"	.39"	3/8"
H1636Z3	1/4"-28	45°	.94"	.30"	.20"	.58"	.25"	.39"	3/8"
H3010Z3	1/4"-28	65°	.78"	.30"	.20"	.66"	.25"	.47"	3/8"
H369575	1/4"-28	65°	.78"	.31"	.20"	.66"	.25"	.47"	3/8"

FREE Material Certifications*

huyett.com/MyAccount/OrderHistory

* Some exclusions apply

Visit your Account Order History at huyett.com to download Free Material, Compliance, and **RoHS/REACH Certifications along with:**



Order Status



Expected Ship Date



Order Tracking Info



Your Favorites



