




COUPLERS

CONVENTIONAL

Hydraulic couplers provide a quick positive leak-proof connection with hydraulic fittings during service. Hydraulic couplers can be used with any type of hydraulic fitting. The hexagonal shape is designed for easy engagement when tightening the coupler.

6304-B

Hydraulic Coupler - Standard
1/8"-27 NPTF
10,000 psi




10,000 PSI

WITH METAL SEAL
NO BALL CHECK
3 JAW CONSTRUCTION
FOR AIR / BATTERY EQUIP.

6304-C

Hydraulic Coupler - Standard
1/8"-27 NPTF
10,000 psi




10,000 PSI

WITH METAL SEAL
NO BALL CHECK
3 JAW CONSTRUCTION
FOR AIR / BATTERY EQUIP.

308730

Hydraulic Coupler - Narrow
1/8"-27 NPTF
10,000 psi




10,000 PSI

RUBBER SEAL
NO BALL CHECK
3 JAW CONSTRUCTION
FOR HAND EQUIPMENT

308730-A

Hydraulic Coupler - Narrow
1/8"-27 NPTF
10,000 psi




10,000 PSI

RUBBER SEAL
3 JAW CONSTRUCTION
FOR HAND EQUIPMENT

B330070

Hydraulic Coupler - Narrow
1/8"-27 NPTF
10,000 psi




10,000 PSI

WITH METAL SEAL
NO BALL CHECK
3 JAW CONSTRUCTION
FOR AIR / BATTERY EQUIP.

B154

Hydraulic Coupler - Narrow
1/8"-27 NPTF
10,000 psi



10,000 PSI

RUBBER SEAL
NO BALL CHECK
3 JAW CONSTRUCTION
FOR AIR / BATTERY EQUIP.

ALEMITE Item #	G.L. HUYETT Order #	Description	Jaws	Equipment Type	Thread	Working Pressure	Ball Check
6304-B	A6304-B	Hydraulic Coupler - Conventional	3 Jaw	Air / Battery	1/8"-27 NPTF	10,000 psi	No
6304-C	A6304-C	Hydraulic Coupler - Conventional	3 Jaw	Air / Battery	1/8"-27 NPTF	10,000 psi	Yes
308730	A308730	Hydraulic Coupler - Conventional	3 Jaw	Hand	1/8"-27 NPTF	10,000 psi	No
308730-A	A308730-A	Hydraulic Coupler - Conventional	3 Jaw	Hand	1/8"-27 NPTF	10,000 psi	Yes
B330070	A330070	Hydraulic Coupler - Conventional	3 Jaw	Air / Battery	1/8"-27 NPTF	10,000 psi	No
B154	AB154	Hydraulic Coupler - Conventional	3 Jaw	Air / Battery	1/8"-27 NPTF	10,000 psi	No