785.392.3017 FAX 785.392.2845



# 1/4"-18 **PTF**

EXCEEDS 72 HR SALT SPRAY. 8,000 PSI MAX PRESSURE.

SAE J534

1/4"-18 PTF fittings, which have 18 threads per inch, are used in large bearings on heavy machinery such as mining equipment and trucks. They are well suited for cold weather environments and for use with heavy lubricants.


# H1627Z3

Straight 1/4"-18 PTF SAE Short Standard Shank




#### H1645Z3

45° Angle 1/4"-18 NPTF Standard Shank




### H1629Z3

65° Angle 1/4"-18 PTF Spl. Extra Short Standard Shank



## H1690Z3

90° Angle 1/4"-18 PTF SAE Short Standard Shank



**1627-B** 1 5050 **L** JD7769

В

\* AVAILABLE IN STAINLESS



ltem #	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H1627Z3	1/4"-18	Straight	.88"	.45"	.34"	_	.52"	_	9/16"
H1645Z3	1/4"-18	45°	1.17"	.37"	.30"	.65"	.52"	.37"	9/16"
H1629Z3 💸	1/4"-18	65°	.97"	.34"	.28"	.84"	.52"	.56"	9/16"
H1690Z3	1/4"-18	90°	.95"	.37"	.23"	.72"	.52"	.44"	9/16"

### OFTEN USED IN...





WITH HEAVY-DUTY LUBRICANTS









John Deere® John Deere® is a registered trademark of Deere and Company, Moline, Illinois.