




























DRIVE TYPE

EXCEEDS 72 HR SALT SPRAY.
8,000 PSI MAX PRESSURE.

SAE J534


Like thread forming fittings, drive type fittings have an advantage of not needing a threaded hole, therefore decreasing the cost of installation. See pages 30-31 for a detailed explanation of the difference between drive type and thread forming fittings. Small diameter shanks are for extra-light-duty applications.

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

<p>H3019Z3 Straight Drive Type ≈ 1/8" Drill Size Standard Shank</p>  <p> 3019  NO BALL CHECK</p>	<p>H1736Z3 Straight Drive Type ≈ 1/8" Drill Size Long Shank</p>  <p> 1736-A  NO BALL CHECK</p>	<p>H5012 Straight Drive Type ≈ 5/32" Drill Size Long Shank</p>  <p> 5012  NO BALL CHECK</p>	<p>H3009Z3 Straight Drive Type ≈ 3/16" Drill Size Short Shank</p>  <p> 3009  NO BALL CHECK</p>
<p>H3005Z3 Straight Drive Type ≈ 3/16" Drill Size Standard Shank</p>  <p> 3005  NO BALL CHECK  700375  M87259</p>	<p>H3006Z3 Straight Drive Type ≈ 3/16" Drill Size Standard Shank</p>  <p> 3006  NO BALL CHECK</p>	<p>H1728Z3 Straight Drive Type ≈ 3/16" Drill Size Long Shank</p>  <p> 1728-B  AVAILABLE IN STAINLESS  5033</p>	<p>H1633Z3 Straight Drive Type ≈ 3/16" Drill Size Long Shank</p>  <p> 1633  NO BALL CHECK</p>

Item #	Drill Diameter	Angle (E)	Overall Length (A)	Shank Length (B)	Overall Width (D)	Swing Clearance (G)	Shoulder Diameter (H)	Ball Check?
H3019Z3	≈ 1/8" Drill	Straight	.47"	.16"	—	—	5/16"	No
H1736Z3	≈ 1/8" Drill	Straight	.56"	.25"	—	—	5/16"	No
H5012	≈ 5/32" Drill	Straight	.56"	.25"	—	—	5/16"	No
H3009Z3	≈ 3/16" Drill	Straight	.39"	.10"	—	—	5/16"	No
H3005Z3	≈ 3/16" Drill	Straight	.47"	.17"	—	—	5/16"	No
H3006Z3	≈ 3/16" Drill	Straight	.48"	.22"	—	—	9/32"	No
H1728Z3	≈ 3/16" Drill	Straight	.52"	.25"	—	—	5/16"	Yes
H1633Z3	≈ 3/16" Drill	Straight	.63"	.25"	—	—	5/16"	No

DRILL SIZES PROVIDED ARE APPROXIMATIONS ONLY. THE EXACT DRILL SIZE FOR DRIVE TYPE FITTINGS MAY VARY WITH YOUR APPLICATION AND MATERIAL. TESTING IS RECOMMENDED TO ENSURE RELIABILITY IN THE FIELD.



All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed. Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2019